

Article	GTX36 HIGH
Category	S3L LG FO SR
Sizes	35 - 48
Width	11
Weight (half pair, sz 42)	650 gr
Metal free	No
Certification	CE



RACER BOOSTER
collection

UPPER	water resistant full grain leather
LINING	extremely breathable polyamide lining. It absorbs moisture quickly and ensures a greater comfort during the whole working day. Optimal resistance to abrasion and anti-bacterial
TOE CAP	Alu-S, aluminium 200J. Ergonomic shape to improve comfort and shoe design. 50% lighter than steel toecaps
ANTI-PERFORATION MIDSOLE	non-magnetic, perforation resistance composite fabric plate. It is 40% lighter and more flexible than steel plate and at the same time guarantees an optimal protection covering 100% of the foot surface. Certified EN 12568:2010
FOOTBED	Memorybed Comfortech, memory foam footbed
SOLE	PU double density with optimal absorption of strains on the vertebral column thanks to the use of soft PU midsole. Ladder Grip approved

UPPER

Water Vapour Permeability	mg/cmq*h	≥ 0,8	5
Water Vapour Coefficient	mg/cmq	≥ 15	46,5

LINING

Water Vapour Permeability	mg/cmq*h	≥ 2	11,1
Water Vapour Coefficient	mg/cmq	≥ 20	97,7

TOECAP

Impact resistance: clearance under the toecap	mm	≥ 14	16
Compression resistance: clearance under the toecap	mm	≥ 14	17

ANTI-PERFORATION MIDSOLE

Penetration resistance (EN ISO 12568:2010)	N	≥ 1100	≥ 1100
--	---	--------	--------

ELECTRICAL RESISTANCE

- wet condition (85% relative humidity)	MΩ	≥ 0,1	19
- dry condition (30% relative humidity)	MΩ	≤ 1000	364

SOLE

Abrasion resistance: relative volume loss	mm ³	≤ 150	42,5
Flexing resistance: cut growth	mm	≤ 4	0
Resistance to fuel oil: volume increase	%	≤ 12	1,7
Energy absorption of seat region	J	≥ 20	27
Slip resistance on	Condition A	≥ 0,31	0,54
ceramic tile with sodium lauryl sulphate	Condition B	≥ 0,36	0,45
Slip resistance on	Condition C	≥ 0,19	0,28
ceramic tile with glycerine	Condition D	≥ 0,22	0,25

MEMORYBED comfortech



ALU-S

SHIELD PRO

