

Article	PB1C WR Brown High
Category	S3 WR SRC
Sizes	36 - 48
Width	11
Weight (half pair, sz 42)	650 gr
Metal free	No
Certification	CE

UPPER	Water resistant nubuck greased leather
WATERPROOF	PERF-DRY120 membrane, totally waterproof and breathable
TOE CAP	steel, 200 Joule, nickel free
ANTI-PERFORATION MIDSOLE	non-magnetic, perforation resistance composite fabric plate. It is 40% lighter and more flexible than steel plate and at the same time guarantees an optimal protection covering 100% of the foot surface. Certified EN 12568:2010
FOOTBED	insole PU 10mm expanded, covered with antibacterial fabric
SOLE	PU double density with optimal absorption of strains on the vertebral column thanks to the use of expanded PU midsole. Maximum stability

Shield PRO

WATERPROOF

PSD
TECHNOLOGY

PERF-DRY120



BASES collection RAIN & COLD

	Requirements EN ISO 20345:2011	Test Results
UPPER		
Water Vapour Permeability	mg/cmq*h ≥ 0,8	3,4
Water Vapour Coefficient	mg/cmq ≥ 15	34,6
LINING		
Water Vapour Permeability	mg/cmq*h ≥ 2	11,1
Water Vapour Coefficient	mg/cmq ≥ 20	97,7
TOECAP		
Impact resistance: clearance under the toecap	mm ≥ 14	14,5
Compression resistance: clearance under the toecap	mm ≥ 14	14,5
ANTI-PERFORATION MIDSOLE		
Penetration resistance (EN ISO 12568:2010)	N ≥ 1100	≥ 1100
ELECTRICAL RESISTANCE		
- wet condition (85% relative humidity)	MΩ ≥ 0,1	14
- dry condition (30% relative humidity)	MΩ ≤ 1000	100
SOLE		
Abrasion resistance: relative volume loss	mm³ ≤ 150	57
Flexing resistance: cut growth	mm ≤ 4	1
Resistance to fuel oil: volume increase	% ≤ 12	0.44
Energy absorption of seat region	J ≥ 20	34
Slip resistance on	7° Heel ≥ 0,13	0.17
steel ground with glycerine	Flat ≥ 0,18	0.22
Slip resistance on	7° Heel ≥ 0,28	0.38
ceramics ground with detergent	Flat ≥ 0,32	0.49

PerfItalia Srl. All rights reserved. The data indicated in this sheet can be modified without notice following evolution in materials and products. Version 1.3

